



PRODUCT FEATURES

- 2000mm long with the cut out for the fan outlet sited horizontally in the centre of the unit
- Modular canopy extraction system suitable for use with gas and electric cooking equipment up to 900mm deep
- Simple to install - just bolt to the wall
- Bright energy-efficient LED lighting provided as standard
- Operates quietly — at just 62 decibels this unit is less noisy than a mobile phone
- Variable fan speed
- Please note that light switches are not supplied by Lincat
- Please note any necessary ductwork and gas interlocks are not supplied by Lincat

A real alternative to expensive bespoke kitchen ventilation, the SmartVent Modular Canopy Extraction Ventilation System is modular in design, robustly constructed, and can help meet challenging installation deadlines. The Ventilation System ensures a comfortable working environment in your kitchen by extracting kitchen smoke and odour. Suitable for fast food outlets, cafes as well as smaller pubs and restaurants, the system operates at just 62 decibels, making it quieter than your mobile phone. This model is designed for the fan outlet to be situated horizontally in the centre of the unit.

A/A FILE NUMBER:

ITEM NUMBER:

WEIGHTS & DIMENSIONS

| | |
|--------|----------|
| Width | 2000 mil |
| Depth | 1200 mil |
| Height | 740 mil |
| Weight | 101 kg |

SHIPPING DETAILS

| | |
|----------------------------|-------------------------|
| Ship Width | 200 cm |
| Ship Depth | 90 cm |
| Ship Height | 136 cm |
| Ship Weight | 111.1 kg |
| Number of Shipment Parcels | 1 |
| Shipping Origin Zip Code | LN6 3QZ, UNITED KINGDOM |
| Quick Ship Product | No |
| Returnable Item | No |

PRODUCT CERTIFICATIONS



ENERGY SPECS

| | | | |
|----------------------------|-------------|--------------------------------------|---------------|
| Primary Energy Source Type | Electricity | Number of Electrical Conductor Wires | 1 |
| Electrical Amps | 5 | Electrical Connection Type | Cord and Plug |
| Electrical Voltage | 230 volts | Electrical Plug Type | UK 3-Pin Plug |
| Electrical Watts | 120 | Number of Electrical Plugs | 1 |
| Electrical Phase | Single | Dedicated Circuit Required | No |
| Kilowatts | 0.12 kW | Energy Saving | No |

ADDITIONAL SPECIFICATIONS

| | |
|------------------------------|-----------------------------|
| Air Movement CFM | 0.58 m ³ /s |
| Control Type | On/Off, Rotary Control Knob |
| Fire Suppression System | No |
| Hood Type | Canopy |
| Ventilation Hood Type Rating | Not Applicable |

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

