

# IMC FROSTAR FR60 GLASS FROSTER [TOP LOAD] - BLACK EXTERIOR - W 600 MM - 0.65 KW

# MODEL: F49/400/BS



The sleek Frostar FR60 chills glasses and liqueurs down to -17°C, enabling commercial bars to create high-quality drinks that look great and stay colder for longer, to boost profits. The FR60 also removes the need for ice, which dilutes drinks and impacts on taste.

The compact, yet robustly built FR60 provides storage for up to 75 standard pint glasses, whilst its top-loading design with sliding cover gives bar staff easy access, so drinks can be served quickly.

With a stylish black exterior, the FR60 is perfectly suited to any bar setting.

### PRODUCT OPTIONS AND ACCESSORIES

- S49/017 Bottle Opener and Cap Catcher for FR60/90 Glass Froster
- BA52/060 Speed Rail for FR60 Glass Froster

### **PRODUCT FEATURES**

- Chills and frosts glasses, to enhance the taste and appearance of drinks
- Rapid chill to -17°C to keep drinks colder for longer
- Efficient design means up to 75 glasses can be chilled at the same time
- Top loading with sliding cover for quick and easy access
- Stylish stainless steel exterior to suit any commercial bar setting
- UK 3 pin plug simply plug in and switch on.







# IMC FROSTAR FR60 GLASS FROSTER [TOP LOAD] - BLACK EXTERIOR - W 600 MM - 0.65 KW

**MODEL: F49/400/BS** 

WEIGHTS & DIMENSIONS	
Width	600 mil
Depth	620 mil
Height	900 mil
Weight	56.5 kg

SHIPPING DETAILS	
Ship Width	68 cm
Ship Depth	68 cm
Ship Height	105 cm
Ship Weight	62.15 kg
Number of Shipment Parcels	1
Ship Method	Small Parcel (FedEx, UPS, DHL)
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

# **PRODUCT CERTIFICATIONS**



ENERGY SPECS	
Primary Energy Type	Electric
Electrical Total Amperage	2.71 A
Electrical Volts	240V
Electrical Total Wattage	650 W
Electrical Kilowatts	0.65 kW
Electrical Phase	1-Phase
Electrical Plug Type	UK 3-Pin Plug

Number of Electrical Plugs	1
Electrical Connection Type	Cord and Plug
Number of Electrical Conductor Wires	1
Dedicated Circuit Required	No
Electrical Remarks	Single
Energy Saving	No

ADDITIONAL SPECIFICATIONS	
Application Type	Undercounter
Capacity Volume	132
Control Type	Digital Touch Pad, Elec- tronic
Defrost Method	Automatic
Insulated	Yes

Number of Shelf Positions	2
Number of Shelves	3
Refrigerant Type	R-290
Temperature Maximum	-17 °C
Type of Lighting	Fluorescent

## **BIDDING SPECIFICATIONS**

Bidding Specifications Not Available.

IMC reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated July 02, 2024










**MODEL: F49/400/BS** 

### **TECHNICAL DRAWING**







IMC reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated July 02, 2024

