



**IMC VENTUS VR60 GLASS FROSTER [FRONT LOAD] - GLASS DOOR  
- BLACK PAINTED FRAME - H 800 MM - W 600 MM**

**MODEL: F49/602/B**



## Ventus

### PRODUCT OPTIONS AND ACCESSORIES

- S76/048 Perforated Shelf - for V60 - 500D
- A12/091/Z1 Wire Shelf - Chrome - for M60 Bottle Cooler

The perfect addition to any commercial bar, the VR60 rapidly chills glasses and liqueurs down to -10°C, to provide high-quality drinks that look great, stay colder for longer and with minimal dilution, as there is no need for ice.

The VR60's shelving provides storage for up to 50 pint glasses, whilst its front-loading design gives bar staff easy access, so drinks can be served quickly.

With a stylish black exterior, the VR60 complements any bar setting.

### PRODUCT FEATURES

- Reduced 800mm height
- Wide range of options available to customise your glass froster, ensure a perfect fit in any bar
- Chills and frosts glasses, to enhance the taste and appearance of drinks
- Dynamic Air Distribution System coupled with efficient compressors and improved insulation ensures superior cooling times
- Rapid chill to -10°C to keep drinks colder for longer.
- Energy efficient EcoSmart controller - at the touch of a button, put the glass froster into its most economical state until next required
- Efficient design means up to 50 pint glasses can be chilled at the same time
- Front loading design ensures fast and easy access to ice cold glasses
- Stylish black painted exterior to suit any commercial bar setting
- UK 3 pin plug - simply plug in and switch on

AIA FILE NUMBER:

ITEM NUMBER:



**IMC VENTUS VR60 GLASS FROSTER [FRONT LOAD] - GLASS DOOR  
- BLACK PAINTED FRAME - H 800 MM - W 600 MM**

**MODEL: F49/602/B**

**WEIGHTS & DIMENSIONS**

|        |         |
|--------|---------|
| Width  | 600 mil |
| Depth  | 500 mil |
| Height | 800 mil |
| Weight | 57.5 kg |

**SHIPPING DETAILS**

|                            |                                |
|----------------------------|--------------------------------|
| Ship Width                 | 67 cm                          |
| Ship Depth                 | 58 cm                          |
| Ship Height                | 106 cm                         |
| Ship Weight                | 63.25 kg                       |
| Number of Shipment Parcels | 1                              |
| Ship Method                | Small Parcel (FedEx, UPS, DHL) |
| Shipping Origin Zip Code   | LN6 3QZ, UNITED KINGDOM        |
| Quick Ship Product         | No                             |

**PRODUCT CERTIFICATIONS**



**ENERGY SPECS**

|                           |               |                                      |               |
|---------------------------|---------------|--------------------------------------|---------------|
| Primary Energy Type       | Electric      | Number of Electrical Plugs           | 1             |
| Electrical Total Amperage | 2.9 A         | Electrical Connection Type           | Cord and Plug |
| Electrical Volts          | 240V          | Number of Electrical Conductor Wires | 1             |
| Electrical Total Wattage  | 667 W         | Dedicated Circuit Required           | No            |
| Electrical Kilowatts      | 0.667 kW      | Electrical Remarks                   | Single        |
| Electrical Phase          | 1-Phase       | Energy Saving                        | Yes           |
| Electrical Plug Type      | UK 3-Pin Plug |                                      |               |

**ADDITIONAL SPECIFICATIONS**

|                  |                               |                           |        |
|------------------|-------------------------------|---------------------------|--------|
| Application Type | Undercounter                  | Number of Shelf Positions | 29     |
| Capacity Volume  | 108 l                         | Number of Shelves         | 2      |
| Control Type     | Digital Touch Pad, Electronic | Refrigerant Type          | R-290  |
| Defrost Method   | Automatic                     | Temperature Maximum       | -10 °C |
| Insulated        | Yes                           | Temperature Minimum       | 2 °C   |
|                  |                               | Type of Lighting          | LED    |

**BIDDING SPECIFICATIONS**

Bidding Specifications Not Available.

IMC reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated  
July 02, 2024








IMC VENTUS VR60 GLASS FROSTER [FRONT LOAD] - GLASS DOOR  
- BLACK PAINTED FRAME - H 800 MM - W 600 MM

MODEL: F49/602/B

TECHNICAL DRAWING



IMC reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated  
July 02, 2024