

## IMC VULTURE 1604X FLOOR-MOUNTED FOOD WASTE DISPOSER - 3 PHASE [4 WIRE] - W 514 MM - 4.0 KW

### MODEL: F54/721



Fast and efficient, the 1604X Waste Disposer is able to dispose of 900kg of food waste per hour and handles up to 1850 covers per sitting, making it ideal for larger hotels, hospitals, universities, prisons and food preparation companies.

An advanced version of the 1604 model, the 1604X is able to switch itself off to save energy and has an automatic rinse function, to prevent nasty odours.

It is suitable for tough waste - red meat bones, cauliflower stalks and fish skins. The free-standing unit can be welded into tabling with a E30/096 hopper rim, for quick loading.

### PRODUCT OPTIONS AND ACCESSORIES

 E30/096 Hopper Rim for 1204/1204X/1604/1604X Food Waste Disposer

### **PRODUCT FEATURES**

- Fast and efficient disposal of up to 900kg of food waste per hour.
- Handles up to 1850 covers per sitting ideal for large kitchens.
- For tough waste (red meat bones, cauliflower stalks and fish skins).
- Free-standing design, but can be welded into tabling with E30/096 hopper rim.
- Manually reversible motor to extend operational life.
- Low-load cut-outs ensure energy and water efficiency.
- Suitable for large kitchens with three-phase, four-wire power supply.







# IMC VULTURE 1604X FLOOR-MOUNTED FOOD WASTE DISPOSER - 3 PHASE [4 WIRE] - W 514 MM - 4.0 KW

## MODEL: F54/721

WEIGHTS & DIMENSIONS	
Width	514 mil
Depth	740 mil
Height	850 mil
Weight	85.5 kg

SHIPPING DETAILS	
Ship Width	79 cm
Ship Depth	54 cm
Ship Height	105 cm
Ship Weight	94.05 kg
Number of Shipment Parcels	1
Ship Method	LTL Common Carrier
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

### **PRODUCT CERTIFICATIONS**



ENERGY SPECS	
Primary Energy Type	Electric
Electrical Total Amperage	8.7 A
Electrical Volts	400V
Electrical Total Wattage	4000 W
Electrical Kilowatts	4 kW
Electrical Phase	3-Phase
Electrical Plug Type	Hardwired

Number of Electrical Plugs	Not Applicable
Electrical Connection Type	Direct Hardwired
Number of Electrical Conductor Wires	1
Dedicated Circuit Required	Yes
Electrical Remarks	Three
Energy Saving	No

ADDITIONAL SPECIFICATIONS	
Airbreak	No
Control Type	On/Off
Meal Waste Servings Processed Per Sitting	1850
Motor Power	5.4 hp
Operator Safety Method	Interlock
Self-Cleaning Capable	No
Waste Processing Capacity Per Hour: Weight	900 kg
Waste Types Processed	Tough (all red meat bones, cauliflower stalks, fish skins)

 $\mbox{IMC}$  reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated July 02, 2024






# IMC VULTURE 1604X FLOOR-MOUNTED FOOD WASTE DISPOSER - 3 PHASE [4 WIRE] - W 514 MM - 4.0 KW


MODEL: F54/721


### **BIDDING SPECIFICATIONS**

Bidding Specifications Not Available.

### **TECHNICAL DRAWING**







IMC reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated July 02, 2024

