



**SP**  
PEELER

**PRODUCT OPTIONS AND ACCESSORIES**

- S58/568 Filter Basket - Integral - for SP Potato Peeler
- S58/569 Interceptor Tank - for SP Potato Peeler [pedestal mounted/2" BSP]
- A29/003 Lid Retaining Strap for SP/VQ Potato Peeler
- S61/168 Stand for SP Potato Peeler
- S58/570 Waste Ejector for SP Potato Peeler [2" BSP]

With a small footprint and quiet motor, the energy-efficient SP25 (3PH) peeler is ideal for medium and large kitchens with a three-phase power supply. Offering the speed and convenience of pre-prepared products, it has the power to peel up to 25kg of vegetables in two minutes - up to 513kg per hour - saving space and time.

Simple and safe to operate, the floor-standing SP25 (3PH) has a low pedestal, for quick and easy discharge of potatoes.

Constructed from rust-proof stainless steel, the SP25 (3PH) is robust and low maintenance, with a heavy-duty belt and pulley drive. Its corrosion-

**PRODUCT FEATURES**

- Able to peel 25kg of potatoes in 2 minutes - up to 513kg per hour
- Upright design with small footprint, ideal for medium and large operations
- Low pedestal for quick and easy discharge of potatoes
- Lubricated, heavy-duty gearbox makes peeling operation smooth and reliable
- Dual position waste outlets and smooth cylinder base for quick, easy cleaning
- Long-lasting, rust-proof plate and replaceable liners for effective peeling
- Suitable for kitchens with three-phase power supply
- WRAS-approved Class A air-break and brass spray nozzle to prevent water escape



**WEIGHTS & DIMENSIONS**

Width	602 mil
Depth	727 mil
Height	1057 mil
Weight	66.5 kg

**SHIPPING DETAILS**

Ship Width	79 cm
Ship Depth	65 cm
Ship Height	155 cm
Ship Weight	73.15 kg
Number of Shipment Parcels	1
Ship Method	Small Parcel (FedEx, UPS, DHL)
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

**PRODUCT CERTIFICATIONS**



**ENERGY SPECS**

Primary Energy Type	Electric	Electrical Plug Type	Hardwired
Electrical Total Amperage	2.1 A	Number of Electrical Plugs	Not Applicable
Electrical Volts	400V	Electrical Connection Type	Direct Hardwired
Electrical Total Wattage	750 W	Number of Electrical Conductor Wires	1
Electrical Kilowatts	0.75 kW	Electrical Remarks	Three
Electrical Phase	3-Phase	Energy Saving	No

**ADDITIONAL SPECIFICATIONS**

Airbreak	Yes
Control Type	On/Off
Hopper Load	25 kg
Motor Power	1 hp
Operator Safety Method	User Guide
Processing Capacity Per Hour	513 kg
Timer Type	Mechanical/Traditional Timer

**BIDDING SPECIFICATIONS**

Bidding Specifications Not Available.

TECHNICAL DRAWING

