

IMC VENTUS V135 BOTTLE COOLER [FRONT LOAD] - FULL FRONTGLASS DOOR - STAINLESS STEEL FRAME - H 900 MM - W 1350 MM - R290

MODEL: F76/370

Ventus

PRODUCT OPTIONS AND ACCESSORIES

• A12/099 Wire Shelf - Chrome - for M135 Bottle Cooler

Designed and manufactured with the highest attention to detail, the sophisticated Ventus V135 bottle cooler is the perfect fit for commercial bars, delivering optimum performance, long-term reliability and minimal operating costs.

The V135 provides flexible storage of up to 310 (330ml) bottles. The polished stainless steel interior and LED lighting enhance display, while the stainless steel exterior cabinet and full front door blend seamlessly into any bar setting.

Its electronic temperature controller, supported by an auto defrost function, provides precise monitoring, ensuring drinks are kept at perfect

PRODUCT FEATURES

- Full front door for seamless integration
- Wide range of options available to customise your bottle cooler, ensure a perfect fit in any bar.
- Elegant, flexible storage for up to 310 bottles
- Dynamic Air Distribution System coupled with efficient compressors and improved insulation ensures superior cooling times.
- Electronic temperature control keeps drinks at the perfect serving temperature
- Energy efficient EcoSmart controller at the touch of a button, put the bottle cooler into its most economical state until next required
- Sleek stainless steel interior and LED lighting to enhance display
- Double glazed doors for enhanced insulation
- UK 3 pin plug allows users to simply plug in and switch on

AIA FILE NUMBER:







IMC VENTUS V135 BOTTLE COOLER [FRONT LOAD] - FULL FRONTGLASS DOOR - STAINLESS STEEL FRAME - H 900 MM - W

MODEL: F76/370

WEIGHTS & DIMENSIONS

Width	1350 mil
Depth	500 mil
Height	900 mil
Weight	109 kg

SHIPPING DETAILS		
Ship Width	142 cm	
Ship Depth	58 cm	
Ship Height	109 cm	
Ship Weight	133 kg	
Number of Shipment Parcels	1	
Ship Method	LTL Common Carrier	
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM	
Quick Ship Product	No	

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Type	Electric
Electrical Total Amperage	2.77 A
Electrical Volts	240V
Electrical Total Wattage	664 W
Electrical Kilowatts	0.664 kW
Electrical Phase	1-Phase
Electrical Plug Type	UK 3-Pin Plug

1
Cord and Plug
1
No
Single
Yes

ADDITIONAL SPECIFICATIONS

Application Type	Undercounter
Capacity: Bottles	310
Capacity Volume	329
Control Type	Digital Touch Pad, Elec- tronic
Defrost Method	Automatic
Insulated	Yes

Number of Shelf Positions	29
Number of Shelves	2
Refrigerant Type	R-290
Temperature Maximum	6 °C
Temperature Minimum	2 °C
Type of Lighting	LED

IMC reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated July 02, 2024






IMC VENTUS V135 BOTTLE COOLER [FRONT LOAD] - FULL FRONTGLASS DOOR - STAINLESS STEEL FRAME - H 900 MM - W

MODEL: F76/370

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING



imc

IMC reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated July 02, 2024

