# imc

#### IMC WASTESTATION COMPACT - 2.95 KW - THREE PHASE

### MODEL: F79/703



Food waste typically represents around 40% of total commercial catering waste. Of this 40%, approximately 77% is liquid. The WasteStation Compact grinds the food waste into fine particles, these particles feed directly into the built-in dewatering system. Through centrifugal action, the WasteStation forces out the excess liquid from the macerated waste.

This "grey water" is fed directly to drain, the resulting solid fraction of the food waste is collected in small, easily managed, lidded bins, ready for onward processing.

#### **PRODUCT OPTIONS AND ACCESSORIES**

A13/159 Waste Scraper for WasteStation Compact

#### **PRODUCT FEATURES**

- A solution for your business process up to 400 kg waste per hour, the equivalent of 850 covers per sitting. As fast as you can input the waste, the WasteStation Compact can process it.
- Reduce your carbon footprint reduce the amount of food waste being sent to landfill. By removing water from food waste this reduces the final volume of waste to be disposed of.
- Save on valuable floor space with a unit which is more compact than bulky alternative models, without having to upgrade to a remote dewaterer.
- Transport savings reduce waste collection costs by up to 80% by reducing the food waste volume and weight requiring collection
- Storage savings by reducing the waste volume, on site waste storage facility requirements are also reduced
- Labour savings reduce staff time processing and managing waste, fast efficient disposal of food waste as and when you need to, with no schedule
- Self-cleaning operation WasteStation can undertake a thorough clean, ensuring the whole system is free of food and grease
- Self-emptying eliminates the need for staff to empty the auger assembly, reducing labour times required to operate the machine. Intelligent electronic sensor detects when the bin is full
- Visual control panel kitchens are a noisy environment, so
  WasteStation incorporates a simple LED display to allow monitoring of the state of the equipment during operation
- Energy savings compact design and short processing times ensure







#### **IMC WASTESTATION COMPACT - 2.95 KW - THREE PHASE**

## **MODEL:** F79/703

WEIGHTS & DIMENSIONS	
Width	600 mil
Depth	700 mil
Height	1044 mil
Weight	165 kg

SHIPPING DETAILS	
Ship Width	120 cm
Ship Depth	80 cm
Ship Height	130 cm
Ship Weight	230 kg
Number of Shipment Parcels	1
Ship Method	LTL Common Carrier
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

#### **PRODUCT CERTIFICATIONS**



ENERGY SPECS		
Primary Energy Type	Electric	Electrical Plug Type
Electrical Amps Per Conductor	L1=4.3; L2=4.3; L3=4.3	Number of Electrical Plugs
Electrical Total Amperage	12.9 A	Electrical Connection Type
Electrical Volts	400V	Number of Electrical Conductor Wires
Electrical Total Wattage	2950 W	Dedicated Circuit Required
Electrical Kilowatts	2.95 kW	Electrical Remarks
Electrical Phase	3-Phase	Energy Saving

ADDITIONAL SPECIFICATIONS			
Airbreak	Yes	Self-Cleaning Capable	Yes
Control Type	On/Off	Waste Compaction Ratio	80 %
Meal Waste Servings Processed Per Sitting	850	Waste Processing Capacity Per Hour: Weight	400 kg
Motor Power	3.95 hp		Medium (small pork/
Operating Noise Level	83 dB	Waste Types Processed	chicken bones, vegeta-
Operator Safety Method	User Guide	Water Consumption Rate	bles and fruit)
			10 l/min

IMC reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated July 02, 2024

Hardwired

1 Yes Three

**Direct Hardwired** 







**MODEL:** F79/703

#### **BIDDING SPECIFICATIONS**

Bidding Specifications Not Available.

IMC reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

