



SILVERLINK 600

PRODUCT OPTIONS AND ACCESSORIES

- CC6 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal with Doors - W 600 mm
- CN6 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 600 mm
- SLS6 Lincat Silverlink 600 Free-standing Floor Stand - for units W 600 mm
- HC6 Lincat Silverlink 600 Free-standing Heated Open-Top Pedestal with Doors - W 600 mm - 0.5 kW
- HCL6 Lincat Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 600 mm - 0.5 kW

PRODUCT FEATURES

- Wet heat bain marie
- Ideal for holding foods for up to 2 hours at serving temperature
- 4x 1/4 and 1x 1/2 150mm deep gastronorms with lids are included
- This wet unit can also be used as a dry bain marie
- Plug and play for an easy installation
- Perfect for safely holding sauces, gravy & pre-cooked foods
- Adjustable temperature control

Do you need to safely hold sauces, soups, gravy and precooked foods for up to two hours at the ideal serving temperature? This Silverlink 600 Electric Wet Heat Bain Marie does just that. Perfect for takeaways, restaurants and mobile caterers, the unit, which can also be used as a dry bain marie, is designed to plug in and play, so you'll be serving delicious dishes in no time. With 4 x 1/4 and 1 x 1/2 150mm deep gastronorms and lids included, the unit also comes with an adjustable temperature control.

A/A FILE NUMBER:

ITEM NUMBER:

WEIGHTS & DIMENSIONS

| | |
|--------|---------|
| Width | 600 mil |
| Depth | 600 mil |
| Height | 290 mil |
| Weight | 18.9 kg |

SHIPPING DETAILS

| | |
|----------------------------|-------------------------|
| Ship Width | 70 cm |
| Ship Depth | 70 cm |
| Ship Height | 49.5 cm |
| Ship Weight | 20.79 kg |
| Number of Shipment Parcels | 1 |
| Shipping Origin Zip Code | LN6 3QZ, UNITED KINGDOM |
| Quick Ship Product | No |
| Returnable Item | No |

PRODUCT CERTIFICATIONS



ENERGY SPECS

| | | | |
|----------------------------|-------------|--------------------------------------|---------------|
| Primary Energy Source Type | Electricity | Number of Electrical Conductor Wires | 1 |
| Electrical Amps | 8.7 | Electrical Connection Type | Cord and Plug |
| Electrical Voltage | 230 volts | Electrical Plug Type | UK 3-Pin Plug |
| Electrical Watts | 2000 | Number of Electrical Plugs | 1 |
| Electrical Phase | Single | Dedicated Circuit Required | No |
| Kilowatts | 2 kW | Energy Saving | No |

ADDITIONAL SPECIFICATIONS

| | | | |
|--------------------------------|----------------------|-------------------|-------------------|
| Control Type | Rotary Control Knob | Modular | Yes |
| Drain | Yes | Mounting Position | Top Mount Drop-In |
| Gastronorm Capacity | 1 x GN1/2, 4 x GN1/4 | Number of Wells | 5 |
| Hot Food Well Application Type | Wet | Waterless | No |
| Insulated | No | Well Shape | Rectangle |

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

