



SILVERLINK 600

PRODUCT OPTIONS AND ACCESSORIES

- CC6 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal with Doors - W 600 mm
- CN6 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 600 mm
- SLS6 Lincat Silverlink 600 Free-standing Floor Stand - for units W 600 mm
- HC6 Lincat Silverlink 600 Free-standing Heated Open-Top Pedestal with Doors - W 600 mm - 0.5 kW
- HCL6 Lincat Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 600 mm - 0.5 kW

PRODUCT FEATURES

- Wet heat bain marie
- Ideal for holding foods for up to 2 hours at serving temperature
- 6 x 1/4 150mm deep gastronorms with lids are included
- This wet unit can also be used as a dry bain marie
- Plug and play for an easy installation
- Perfect for safely holding sauces, gravy & pre-cooked foods
- Adjustable temperature control

Do you need to safely hold sauces, soups, gravy and precooked foods for up to two hours at the ideal serving temperature? This Silverlink 600 Electric Wet Heat Bain Marie does just that. Perfect for takeaways, restaurants and mobile caterers, the unit, which can also be used as a dry bain marie, is designed to plug in and play, so you'll be serving delicious dishes in no time. With 6 x 1/4 150mm deep gastronorms and lids included, the unit also comes with an adjustable temperature control.

A/A FILE NUMBER:

ITEM NUMBER:



LINCAT SILVERLINK ELECTRIC COUNTER-TOP BAIN MARIE - WET HEAT - GASTRONORMS - BASE + DISH PACK - W 600 MM - 2.0 KW

MODEL: BM6CW

WEIGHTS & DIMENSIONS

Width	600 mil
Depth	600 mil
Height	290 mil
Weight	19.1 kg

SHIPPING DETAILS

Ship Width	70 cm
Ship Depth	70 cm
Ship Height	49.5 cm
Ship Weight	21.01 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Source Type	Electricity	Number of Electrical Conductor Wires	1
Electrical Amps	8.7	Electrical Connection Type	Cord and Plug
Electrical Voltage	230 volts	Electrical Plug Type	UK 3-Pin Plug
Electrical Watts	2000	Number of Electrical Plugs	1
Electrical Phase	Single	Dedicated Circuit Required	No
Kilowatts	2 kW	Energy Saving	No

ADDITIONAL SPECIFICATIONS

Control Type	Rotary Control Knob	Modular	Yes
Drain	Yes	Mounting Position	Top Mount Drop-In
Gastronorm Capacity	6 x GN1/4	Number of Wells	6
Hot Food Well Application Type	Wet	Waterless	No
Insulated	No	Well Shape	Rectangle

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

