



**SILVERLINK 600**

Whether you're cooking eggs, bacon, burgers or vegetables, the versatile Silverlink 600 Electric Griddle won't let you down. The hard-wearing 12 mm thick steel plate provides even heat distribution and excellent heat retention, while the griddle is thermostatically controlled to give accurate temperatures during the cooking process for consistent results. The griddle, which comes with an extra powered element to ensure maximum output for busy kitchens, is perfect for cafes, pubs and restaurants. It's designed to plug in and play, so you'll be cooking mouthwatering dishes in no time.

**PRODUCT OPTIONS AND ACCESSORIES**

- SB4 450 GRIDDLE SPLASHB
- CC4 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal with Doors - W 450 mm
- CN4 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 450 mm
- SLS4 Lincat Silverlink 600 Free-standing Floor Stand - for units W 450 mm
- HC4 Lincat Silverlink 600 Free-standing Heated Open-Top Pedestal with Doors - W 450 mm - 0.5 kW
- HCL4 Lincat Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 450 mm - 0.5 kW

**PRODUCT FEATURES**

- Extra powered element for maximum output for a busy kitchen
- Hard wearing 12 mm thick machined steel plate providing even heat distribution and excellent heat retention
- Thermostatically controlled to give accurate temperatures during the cooking process for consistent results
- Removable front drainer drawer which also makes for easy cleaning. Ideal for busy establishments
- The plate is fully welded into the frame to prevent leaks and places where food and carbon can build up

**WEIGHTS & DIMENSIONS**

Width	450 mil
Depth	600 mil
Height	330 mil
Weight	32 kg

**SHIPPING DETAILS**

Ship Width	70 cm
Ship Depth	55 cm
Ship Height	57 cm
Ship Weight	35.2 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

**PRODUCT CERTIFICATIONS**



**ENERGY SPECS**

Primary Energy Source Type	Electricity	Number of Electrical Conductor Wires	1
Electrical Amps	16.1	Electrical Connection Type	Cord and Plug
Electrical Voltage	230 volts	Electrical Plug Type	UK 3-Pin Plug
Electrical Watts	3700	Number of Electrical Plugs	1
Electrical Phase	Single	Dedicated Circuit Required	No
Kilowatts	3.7 kW	Energy Saving	No

**ADDITIONAL SPECIFICATIONS**

Control Type	Rotary Control Knob	Number of Heating Zones	2
Cooking Area Plate Depth	405 mm	Plate Shape	Rectangle
Cooking Area Plate Width	412 mm	Plate Thickness	12 mm
Cooking Plate Finish Material Type	Polished Steel	Temperature Maximum	250 °C
Legs or Casters	Not Applicable	Temperature Minimum	50 °C
Lower Platen Surface Type (multi-select)	Smooth	Thermostat Element Location	Under Plate Mount
Number Of Controls	2		

**BIDDING SPECIFICATIONS**

Bidding Specifications Not Available.

TECHNICAL DRAWING

