



The M3F enables end users to benefit from a quality UK manufactured product at a competitive price.

The boiler utilises our popular FilterFlow cartridges and is connected to the mains water supply to provide end users with a continuous stream of top quality boiling water.

For ease of installation the boilers come with a UK 3 pin plug and are fixed to the wall with just three screws.

#### PRODUCT OPTIONS AND ACCESSORIES

- DP10 DESCALER POWDER
- FC04 EBFX WATER FILTER - FROM 2015

#### PRODUCT FEATURES

- High quality boiling water on tap 24 hours a day
- Wall mounted, compact design
- Easy installation – UK 3 pin plug and three screws
- Built-in water filtration system improves water quality
- High volume, easy change FilterFlow cartridge
- Adjustable water temperature from 70°- 96°C
- Precise electronic temperature control system
- LCD information panel
- Enhanced multi-level diagnostics

**WEIGHTS & DIMENSIONS**

Width	300 mil
Depth	269 mil
Height	398 mil
Weight	8.9 kg

**SHIPPING DETAILS**

Ship Width	41 cm
Ship Depth	63 cm
Ship Height	35 cm
Ship Weight	9.79 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

**PRODUCT CERTIFICATIONS**



**ENERGY SPECS**

Primary Energy Source Type	Electricity	Number of Electrical Conductor Wires	1
Electrical Amps	13	Electrical Connection Type	Cord and Plug
Electrical Voltage	230 volts	Electrical Plug Type	UK 3-Pin Plug
Electrical Watts	3000	Number of Electrical Plugs	1
Electrical Phase	Single	Dedicated Circuit Required	No
Kilowatts	3 kW	Energy Saving	No

**ADDITIONAL SPECIFICATIONS**

Capacity Volume	3.5 l	Internal Filter	Yes
Control Type	Electronic	Rapid Draw Off Hot	3.5 l
Dispense Actuation Method	Lever	Rapid Draw Off Hot Cups	18 C
Drip Pan	No	Temperature Maximum	96 °C
Hourly Hot Water Output	28 l	Temperature Minimum	70 °C
Hourly Number of Hot Cups	140		

**BIDDING SPECIFICATIONS**

Bidding Specifications Not Available.

#### TECHNICAL DRAWING

