



Opus 800

With a half ribbed plate option for attractive branding presentation marks, the Opus 800 Electric Ribbed Plate Griddle is designed to create appetizing food accurately. The griddle comes with a precise thermostatic control up to 300°C for consistent results and an economical operation. Perfect for any busy commercial kitchen, it utilizes a maximised cooking area, with the griddle plates to the sides of the unit.

PRODUCT OPTIONS AND ACCESSORIES

-
-
- OA8914/C Lincat Opus 800 Free-standing Floor Stand with Castors - for units W 900 mm
- OA8914 Lincat Opus 800 Free-standing Floor Stand with Legs - for units W 900 mm
- OA8973/C Lincat Opus 800 Free-standing Pedestal with Doors and Castors - for units W 900 mm
- OA8973 Lincat Opus 800 Free-standing Pedestal with Doors and Legs - for units W 900 mm
- LK11 OPUS 800 LONG LEG KIT

PRODUCT FEATURES

- Half ribbed plate option for attractive branding presentation marks
- Maximised cooking area, griddle plates sit flush to the sides of the unit
- Precise thermostatic control up to 300°C for consistent results and economical operation

WEIGHTS & DIMENSIONS

Width	900 mil
Depth	800 mil
Height	428 mil
Weight	109 kg

SHIPPING DETAILS

Ship Width	100 cm
Ship Depth	85 cm
Ship Height	64 cm
Ship Weight	119.9 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Source Type	Electricity	Number of Electrical Conductor Wires	1
Electrical Amps	Single Phase 52.2/Three Phase L1=17.4; L2=17.4; L3=17.4	Electrical Connection Type	Direct Hardwired
Electrical Voltage	230 volts/400 volts	Electrical Plug Type	Hardwired
Electrical Watts	12000	Number of Electrical Plugs	Not Applicable
Electrical Phase	Single, Three	Dedicated Circuit Required	Yes
Kilowatts	12 kW	Energy Saving	No

ADDITIONAL SPECIFICATIONS

Control Type	Rotary Control Knob	Lower Platen Surface Type (multi-select)	Smooth and Grooved
Cooking Area Plate Depth	890 mm	Number Of Controls	2
Cooking Area Plate Width	600 mm	Number of Heating Zones	2
Cooking Plate Finish Material Type	Half Grooved Steel Plate	Plate Shape	Rectangle
Food Production Rate	140 x 225g [8oz] steaks [chilled] per hour	Plate Thickness	15 mm
Legs or Casters	Not Applicable	Temperature Maximum	300 °C
		Temperature Minimum	90 °C
		Thermostat Element Location	Under Plate Mount

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

