



Opus 800

PRODUCT OPTIONS AND ACCESSORIES

- OA8986 KEEP WARM SHELF - OE8405
- OA8917/C Lincat Opus 800 Free-standing Floor Stand with Castors - for units W 600 mm
- OA8917 Lincat Opus 800 Free-standing Floor Stand with Legs - for units W 600 mm
- OA8972/C Lincat Opus 800 Free-standing Pedestal with Doors and Castors - for units W 600 mm
- OA8972 Lincat Opus 800 Free-standing Pedestal with Doors and Legs - for units W 600 mm

PRODUCT FEATURES

- Three multiple heat zones can form differing temperature on the same surface, allowing you to cook chicken fillets only inches away from steaks. Individual zones can be turned off during quiet periods.
- Uniquely designed radiant's add just the right level of flaring to enhance flavour whilst the heavy duty branding grids add the appetising finish
- Removable, durable, segmented cast iron grids impart attractive branding marks to food
- Hinging, interlocked elements and integral water bath makes cleaning easier
- Plumbed to water supply for quick and easy filling of water bath with alternative manual fill facility

Embrace the unique versatility of the Opus 800 Three-Zone Electric Chargrill, which provides three heat zones that can form differing temperature on the same surface, allowing you to cook chicken fillets only inches away from steaks. Create succulent dishes with a distinctive chargrilled flavour and branded appearance with the heavy-duty branding grids and innovative radiants that add just the right level of flaring. Perfect for any busy commercial kitchen, the chargrill has hinged, interlocked elements, while the integral water bath makes cleaning easier.

A/A FILE NUMBER:

ITEM NUMBER:

WEIGHTS & DIMENSIONS

Width	600 mil
Depth	817 mil
Height	415 mil
Weight	57 kg

SHIPPING DETAILS

Ship Width	85 cm
Ship Depth	70 cm
Ship Height	64 cm
Ship Weight	62.7 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Source Type	Electricity	Number of Electrical Conductor Wires	1
Electrical Amps	L1=12.2; L2=12.2; L3=12.2	Electrical Connection Type	Direct Hardwired
Electrical Voltage	400 volts	Electrical Plug Type	Hardwired
Electrical Watts	8400	Number of Electrical Plugs	Not Applicable
Electrical Phase	Three	Dedicated Circuit Required	Yes
Kilowatts	8.4 kW	Energy Saving	No

ADDITIONAL SPECIFICATIONS

Control Type	Mechanical, Rotary Control Knob	Grate Type	Cast Iron
Cooking Area Plate Depth	530 mm	Number Of Controls	3
Cooking Area Plate Width	560 mm	Number of Heating Elements	3
Food Production Rate	48 x 225g [8oz] steaks [chilled] per hour	Number of Heating Zones	3
		Temperature Maximum	300 °C
		Temperature Minimum	90 °C

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

