



*Opus* 800

#### PRODUCT OPTIONS AND ACCESSORIES

- BA82 BASKET LARGE
- OF2 Oil filter kit - size 2
- LK02 OPUS 350 LEG KIT
- OA8955 SPLASHGUARD FRYERS - OPUS 800

#### PRODUCT FEATURES

- Accurate thermostatic control up to 190°C for consistent results and safe operation
- Convenient piezo ignition
- Externally fired heating gives easy access for cleaning tanks

Fry delicious food accurately with this Opus 800 Single-Tank Free Standing Single-Tank Gas Fryer which comes with an accurate thermostatic control for consistent results and safe operation. The fryer is ideal for a variety of busy commercial kitchens, whether it's a large pub or a restaurant. Featuring convenient piezo ignition, the fryer has externally fired heating which allows for easy access for cleaning the tanks.

A/A FILE NUMBER:

ITEM NUMBER:

**WEIGHTS & DIMENSIONS**

Width	400 mm
Depth	800 mil
Height	1020 mm
Weight	88.1 kg

**SHIPPING DETAILS**

Ship Width	85 cm
Ship Depth	800 cm
Ship Height	122 cm
Ship Weight	96.91 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

**PRODUCT CERTIFICATIONS**



**ENERGY SPECS**

Primary Energy Source Type	Gas	Gas Inlet Size	0.5 in
Kilowatts	23 kW	Gas Inlet Pressure Required	20 mBar
Electrical Connection Type	Not Applicable	Gas Total BTUs	78476 BTU
Electrical Plug Type	Not Applicable	Gas Consumption at Max Use Per Hour	2.19 m <sup>3</sup>
Number of Electrical Plugs	Not Applicable	Total Heat Input at Max Use	23 kW, 78479 BTU per hour
Dedicated Circuit Required	Yes	Energy Saving	No
Gas Type	Natural Gas		

**ADDITIONAL SPECIFICATIONS**

Auto Oil Top-Off	No	Number of Burners	2
Basket Lift Type	Not Applicable	Number of Vats (batteries)	1
Control Type	Mechanical	Total Oil Capacity (volume)	16 l
Food Production Rate	28kg chips - 12mm [frozen], 34kg chips - 12mm [chilled] per hour	Oil Reclamation	No
Fryer Type	Open Pot	Oil Temperature Control	Mechanical
Integrated Filtration	No	Pumped Oil Filtration	No
Number of Baskets	2	Split Pot	No
		Temperature Maximum	190 °C
		Temperature Minimum	90 °C
		Vat 1 Oil Capacity (volume)	16 l

**BIDDING SPECIFICATIONS**

Bidding Specifications Not Available.

**TECHNICAL DRAWING**

