



Opus 800

PRODUCT OPTIONS AND ACCESSORIES

- OF2 Oil filter kit - size 2
- LK02 OPUS 350 LEG KIT
- OA8955 SPLASHGUARD FRYERS - OPUS 800
- BA159 WIRE BASKET

PRODUCT FEATURES

- Accurate thermostatic control up to 190°C for consistent results and safe operation
- Convenient piezo ignition
- Externally fired heating gives easy access for cleaning tanks

Fry delicious food accurately with this Opus 800 Single-Tank Free Standing Single-Tank Gas Fryer which comes with an accurate thermostatic control for consistent results and safe operation. The fryer is ideal for a variety of busy commercial kitchens, whether it's a large pub or a restaurant. Featuring convenient piezo ignition, the fryer has externally fired heating which allows for easy access for cleaning the tanks.

A/A FILE NUMBER:

ITEM NUMBER:

WEIGHTS & DIMENSIONS

Width	600 mm
Depth	800 mil
Height	1020 mm
Weight	113.5 kg

SHIPPING DETAILS

Ship Width	70 cm
Ship Depth	800 cm
Ship Height	122 cm
Ship Weight	124.85 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Source Type	Gas
Kilowatts	30 kW
Number of Electrical Conductor Wires	1
Electrical Connection Type	Direct Hardwired
Electrical Plug Type	Hardwired
Number of Electrical Plugs	Not Applicable
Dedicated Circuit Required	Yes
Gas Type	Propane

Gas Inlet Size	0.5 in
Gas Inlet Pressure Required	37 mBar
Gas Total BTUs	102360 BTU
Gas Consumption at Max Use Per Hour	2.14 m ³
Total Heat Input at Max Use	30 kW, 102364 BTU per hour
Energy Saving	No

ADDITIONAL SPECIFICATIONS

Auto Oil Top-Off	No
Basket Lift Type	Not Applicable
Control Type	Mechanical
Food Production Rate	22kg chips - 12mm [frozen], 32kg chips - 12mm [chilled] per hour
Fryer Type	Open Pot
Integrated Filtration	No
Number of Baskets	2

Number of Burners	2
Number of Vats (batteries)	1
Total Oil Capacity (volume)	25 l
Oil Reclamation	No
Oil Temperature Control	Mechanical
Pumped Oil Filtration	No
Split Pot	No
Temperature Maximum	190 °C
Temperature Minimum	90 °C
Vat 1 Oil Capacity (volume)	25 l

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

