

MODEL: OG8402/P



Embrace the unique power and versatility of the Opus 800 Five-Zone Gas Chargrill, which provides five heat zones capable of maintaining different temperatures on the same surface, allowing you to cook chicken fillets only inches away from steaks. Highly powerful infrared burners respond quicker and heat faster than standard burners, allowing you to increase your output and achieve energy savings at the same time. Perfect for any busy commercial kitchen, the chargrill comes with heavy-duty cast iron branding grids with a reversible design for uninterrupted cooking and self cleaning at maximum power. There's also flame failure protection for added safety.



PRODUCT OPTIONS AND ACCESSORIES

- OA8951/C Lincat Opus 800 Free-standing Floor Stand with Castors for units W 900 mm
- OA8951 Lincat Opus 800 Free-standing Floor Stand with Legs for units W 900 mm
- RC03M RADIANT COVER OPUS 800

PRODUCT FEATURES

- Five multiple heat zones can form differing temperature on the same surface, allowing you to cook chicken fillets only inches away from steaks. Individual zones can be turned off during quiet periods.
- Highly powerful infra-red burners respond quicker and heat faster than standard burners allowing you to increase your output and achieve energy savings
- Heavy-duty cast iron branding grids with reversible design, for uninterrupted cooking and self cleaning at maximum power
- Flame failure protection
- Heavy duty radiant caps protect burners









MODEL: OG8402/P

WEIGHTS & DIMENSIONS	
Width	900 mm
Depth	806 mil
Height	653 mm
Weight	115 kg

SHIPPING DETAILS	
Ship Width	100 cm
Ship Depth	806 cm
Ship Height	79 cm
Ship Weight	126.5 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

PRODUCT CERTIFICATIONS



ENERGY SPECS			
Primary Energy Source Type	Gas	Gas Inlet Size	0.5 in
Kilowatts	21 kW	Gas Inlet Pressure Required	37 mBar
Electrical Connection Type	Not Applicable	Gas Total BTUs	71652 BTU
Electrical Plug Type	Not Applicable	Gas Consumption at Max Use Per Hour	1.5 m ³
Number of Electrical Plugs	Not Applicable	Total Heat Input at Max Use	21 kW, 71652 BTU per
Dedicated Circuit Required	Yes		hour
Gas Type	Propane	Energy Saving	Yes

ADDITIONAL SPECIFICATIONS			
Base Type	Not Applicable	Grate Type	Cast Iron
Burner Material	Stainless Steel	Ignition Type	Pilot Light
Charbroiler Type	Countertop	Legs or Casters	Not Applicable
Control Type	Mechanical, Rotary	Number of Burners	5
	Control Knob	Number Of Controls	5
Cooking Area Plate Depth	620 mm	Number of Heating Zones	5
Cooking Area Plate Width	800 mm	Radiant Material	Ceramic Plaque
Food Production Rate	118 x 225g [8oz] steaks [chilled] per hour	Slide Out Warming Rack	No
		Towel Bar	No

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 23, 2024







MODEL: OG8402/P


BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING







Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 23, 2024

