

MODEL: P8P3



Helping to cater in demanding environments such as cafeterias, canteens and restaurants, the Panther 800 Series Hot Cupboard is perfect for plating and garnishing and as a pass to front of house staff, while it also provides extra workspace or can be used as a mobile workstation. The unit is fan assisted, providing even heat distribution, fast heat up and recovery times, and lower energy usage. Fully 1/1 GN compatible, this unit accomodates 3 x 1/1 GN containers up to 150mm deep, while the thermostatically controlled bain marie top can be operated with wet or dry heat. An accurate digital electronic control of the hot cupboard temperature, adjustable between 20 and 99°C, ensures compliance with food hygiene regulations.

### PRODUCT OPTIONS AND ACCESSORIES

- PLK/S PANTHER LEG KIT FOR CONVERSION IN THE FIELD
- PPB8 PPB8 ADDITIONAL PUSHBAR

### **PRODUCT FEATURES**

- Helping to cater in demanding environments such as cafeterias, canteens and restaurants
- Fan assisted hot cupboard provides even heat distribution, fast heat up and recovery times, and lower energy usage. Four shelf positions allow adjustment to meet individual needs.
- Fully 1/1 GN compatible hot cupboard for operational efficiency. Units available to take 3 x 1/1 GN containers up to 150mm deep.
- Accurate digital electronic control of the hot cupboard temperature, adjustable between 20 and 99 °C, ensures compliance with food hygiene regulations
- Double skinned construction provides efficient heat retention and a cool to touch exterior - safe and energy efficient. Removable doors and shelves allow access to the fully stainless steel interior for easy
- Supplied with two heavy duty multi-section chrome plated rod shelves capable of taking the heaviest loads







# LINCAT PANTHER 800 SERIES FREE-STANDING HOT CUPBOARD -**PLAIN TOP - W 1205 MM - 1.5 KW**

MODEL: P8P3

| WEIGHTS & DIMENSIONS |          |
|----------------------|----------|
| Width                | 1205 mil |
| Depth                | 850 mil  |
| Height               | 900 mil  |
| Weight               | 113 kg   |

| SHIPPING DETAILS           |                         |
|----------------------------|-------------------------|
| Ship Width                 | 123 cm                  |
| Ship Depth                 | 90 cm                   |
| Ship Height                | 110 cm                  |
| Ship Weight                | 124.3 kg                |
| Number of Shipment Parcels | 1                       |
| Shipping Origin Zip Code   | LN6 3QZ, UNITED KINGDOM |
| Quick Ship Product         | No                      |
| Returnable Item            | No                      |

# **PRODUCT CERTIFICATIONS**



| ENERGY SPECS               |             |                                      |               |
|----------------------------|-------------|--------------------------------------|---------------|
| Primary Energy Source Type | Electricity | Number of Electrical Conductor Wires | 1             |
| Electrical Amps            | 6.5         | Electrical Connection Type           | Cord and Plug |
| Electrical Voltage         | 230 volts   | Electrical Plug Type                 | UK 3-Pin Plug |
| Electrical Watts           | 1500        | Number of Electrical Plugs           | 1             |
| Electrical Phase           | Single      | Dedicated Circuit Required           | No            |
| Kilowatts                  | 1.5 kW      | Energy Saving                        | No            |

| ADDITIONAL SPECIFICATIONS |                          |                     |                  |
|---------------------------|--------------------------|---------------------|------------------|
| Cart Style                | Plated Meals and Pans    | Number of Shelves   | 2                |
| Control Type              | Digital Touch Pad, Elec- | Plate Capacity      | 316              |
|                           | tronic                   | Plate Diameter      | 11.25" to 12.75" |
| Heating System            | Electric                 | Shelf Depth         | 512 mm           |
| Legs or Casters           | Casters                  | Shelf Width         | 980 mm           |
| Number of Doors           | 2                        | Temperature Maximum | 99 °C            |
| Number of Shelf Positions | 4                        | Temperature Minimum | 20 °C            |

# **BIDDING SPECIFICATIONS**

Bidding Specifications Not Available.

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 23, 2024










**MODEL: P8P3** 

# **TECHNICAL DRAWING**







Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.