

LINCAT PHOENIX ELECTRIC FREE-STANDING INDUCTION OVEN RANGE - 4-ZONE - W 600 MM - 11.4 KW [1 OR 3-PHASE]

MODEL: PHER02



With four 1.85kW induction zones and a large three 1/1GN capacity oven, the Phoenix Electric Induction Oven is all about flexibility. Need intense heat quickly? Two zones can be boosted to 3kW for up to ten minutes, meaning you'll be cooking delicious dishes in no time. Power to the other two zones will drop during the boost period. Ideal for care homes and schools, as well as smaller pubs and restaurants, the oven is easy to clean and offers incredible efficiency by automatically cutting power when no pan is present.

PRODUCT FEATURES

- Four 1.85kW zones. When you need intense heat to get you cooking fast two zones can be boosted to 3kW for up to 10 minutes. Power to the other two zones will drop during the boost period.
- Large 3 x GN1/1 capacity fan assisted oven enabling three different foods to be cooked simultaneously
- Incredible efficiency, automatically cutting power when no pan is present, reducing running costs and providing a more comfortable kitchen environment
- Easy to clean, heavy duty 6mm thick high impact resistant glass ceramic surface
- Highly insulated oven reducing heat loss and ensuring a more consistent temperature
- Suitable for single or three phase applications







LINCAT PHOENIX ELECTRIC FREE-STANDING INDUCTION OVEN RANGE - 4-ZONE - W 600 MM - 11.4 KW [1 OR 3-PHASE]

MODEL: PHER02

WEIGHTS & DIMENSIONS	
Width	600 mil
Depth	805 mil
Height	900 mil
Weight	109 kg

SHIPPING DETAILS	
Ship Width	70 cm
Ship Depth	85 cm
Ship Height	105 cm
Ship Weight	119.9 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

PRODUCT CERTIFICATIONS



ENERGY SPECS	
Primary Energy Source Type	Electricity
Electrical Amps	Single Phase 49.6/Three Phase L1=17.4; L2=16.1; L3=16.1
Electrical Voltage	230 volts/400 volts
Electrical Watts	11400
Electrical Phase	Single, Three
Kilowatts	11.4 kW

Number of Electrical Conductor Wires	1
Electrical Connection Type	Direct Hardwired
Electrical Plug Type	Hardwired
Number of Electrical Plugs	Not Applicable
Dedicated Circuit Required	Yes
Energy Saving	Yes

ADDITIONAL SPECIFICATIONS	
Control Type	Rotary Control Knob
Cooking Plate Finish Material Type	Ceran Glass
Exterior Finish Color	Stainless Steel
Exterior Trim Finish Color	Stainless Steel
Gastronorm Capacity	3 x GN1/1
Heat Source Type	Induction
High Altitude Kit Available	No
Number of Heating Zones	4
Number of Hot Top Burners	4
Number of Induction Burners	4
Number of Shelf Positions	5

Number of Shelves	3
Open or Sealed Burners	Not Applicable
Orientation Of Burners	Front-To-Back
Oven Power Rating	4 kW
Oven Temperature Maximum	250 °C
Oven Temperature Minimum	50 °C
Shelf Depth	530 mm
Shelf Width	480 mm
Temperature Maximum	250 °C
Temperature Minimum	50 °C
Watts Per Flement	1850

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 23, 2024





LINCAT PHOENIX ELECTRIC FREE-STANDING INDUCTION OVEN RANGE - 4-ZONE - W 600 MM - 11.4 KW [1 OR 3-PHASE]

MODEL: PHER02

SELECT COOKING EQUIPMENT	NUMBER OF		POWER RATING	ARRANGE- MENT	WIDTH	DEPTH
Induction Burner 1		4		Center	190 mm	190 mm
SELECT BASE EQUIPMENT	NUMBER OF		CUBIC CAPACITY EACH	WIDTH	DEPTH	HEIGHT
Standard Oven 1		1		495 mm	530 mm	405 mm

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

January 23, 2024

Document Auto-Generated










MODEL: PHER02

TECHNICAL DRAWING







Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 23, 2024

