



SEAL

Tempt customers with perfect pizzas, pies and pastries on the Seal Upright Heated Merchandiser's static chrome plated rack. The rack doesn't only make for an attractive display, but is also easy to clean. Perfect for busy establishments, the unit, which is accessed from the back, comes with thermostatic control up to 95°C and a humidity feature which prevents food from drying out and so keeping it in optimum condition for longer.

A/A FILE NUMBER:

PRODUCT FEATURES

- Robust stainless steel construction - hygienic and easy to clean
- Minimum food holding temperature of 72°C
- Thermostatic control up to 95°C
- Chrome plated rack for attractive appearance and ease of cleaning
- Humidity feature keeps food in perfect condition for longer, minimising waste
- Suitable for back-service applications

ITEM NUMBER:



LINCAT SEAL COUNTER-TOP UPRIGHT HEATED MERCHANDISER - STATIC RACK - SINGLE DOOR - W 562 MM - 1.4 KW

MODEL: UMS50

WEIGHTS & DIMENSIONS

Width	562 mil
Depth	562 mil
Height	783 mil
Weight	48 kg

SHIPPING DETAILS

Ship Width	69.5 cm
Ship Depth	66.5 cm
Ship Height	97.6 cm
Ship Weight	52.8 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Source Type	Electricity	Number of Electrical Conductor Wires	1
Electrical Amps	6.12	Electrical Connection Type	Cord and Plug
Electrical Voltage	230 volts	Electrical Plug Type	UK 3-Pin Plug
Electrical Watts	1400	Number of Electrical Plugs	1
Electrical Phase	Single	Dedicated Circuit Required	No
Kilowatts	1.4 kW	Energy Saving	No

ADDITIONAL SPECIFICATIONS

Control Type	Mechanical	Rack Type	Static
Display Case Front Design Style	Straight Glass Front	Shelf Depth	446 mm
Display Case Service Type	Front of House Service	Shelf Width	420 mm
Display Case Type	Heated	Temperature Maximum	95 °C
Heated Base	Yes	Temperature Minimum	72 °C
Lighted	Yes	Type of Lighting	Fluorescent
Number of Shelves	3		

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

