



**SILVERLINK 600**

Cook with confidence with the Silverlink 600 Electric Oven, which comes with a fan assisted oven for superior heat distribution and reduced cooking times. Ideal for care homes as well as smaller pubs and restaurants, the oven, which accommodates 2/3 GN dishes and boasts a rapid cool down feature, guarantees excellent performance and optimum efficiency operating from a 13A plug. Multi-use, there are four shelf positions with two removable shelves, while the oven is also able to support Silverlink 600 counter top units such as boiling tops, bains marie, griddles and work tops.

**PRODUCT OPTIONS AND ACCESSORIES**

- SLS6V Lincat Silverlink 600 Free-standing Floor Stand - for V6 Series Ovens - W 600 mm
- V6/T V6 TOP COVER - ACCESSORY ONLY

**PRODUCT FEATURES**

- Fan assisted oven for superior heat distribution and reduced cooking times
- Excellent performance and optimum efficiency operating from a 13A plug
- Accommodates 2/3 gastronorms
- Rapid cool down feature
- Four shelf positions with two removable shelves
- Able to support Silverlink 600 counter top units such as boiling tops, bains marie, griddles and work tops
- Stainless steel interior with radiused corners and removable side shelf supports for easy cleaning

A/A FILE NUMBER:

ITEM NUMBER:

**WEIGHTS & DIMENSIONS**

Width	600 mil
Depth	623 mil
Height	674 mil
Weight	45.1 kg

**SHIPPING DETAILS**

Ship Width	70.3 cm
Ship Depth	70.3 cm
Ship Height	102.3 cm
Ship Weight	49.61 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

**PRODUCT CERTIFICATIONS**



**ENERGY SPECS**

Primary Energy Source Type	Electricity	Number of Electrical Conductor Wires	1
Electrical Amps	13	Electrical Connection Type	Cord and Plug
Electrical Voltage	240 volts	Electrical Plug Type	UK 3-Pin Plug
Electrical Watts	3000	Number of Electrical Plugs	1
Electrical Phase	Single	Dedicated Circuit Required	No
Kilowatts	3 kW	Energy Saving	No

**ADDITIONAL SPECIFICATIONS**

Control Type	Mechanical, Rotary Control Knob	Door Type	Solid
Cooking Chamber Depth	335 mm	Fan Assisted	Yes
Cooking Chamber Height	420 mm	Gastronorm Capacity	1 x GN2/3
Cooking Chamber Width	470 mm	Number of Wire Racks	3
Cooking Rack Depth	335 mm	Temperature Maximum	250 °C
Cooking Rack Width	455 mm	Temperature Minimum	50 °C

**BIDDING SPECIFICATIONS**

Bidding Specifications Not Available.

#### TECHNICAL DRAWING

