

### IMC VENTUS V90 BOTTLE COOLER [FRONT LOAD] - GLASS DOOR -BLACK PAINTED FRAME - H 850 MM - W 900 MM - R290

## **MODEL: F76/251/B**



**Ventus** 

Designed and manufactured with the highest attention to detail, the sophisticated Ventus V90 bottle cooler is the perfect fit for commercial bars, delivering optimum performance, long-term reliability and minimal operating costs.

The V90 provides flexible storage of up to 117 (330ml) bottles. The polished stainless steel interior and LED lighting enhance display, while the black painted exterior cabinet blends seamlessly into any bar setting.

Its electronic temperature controller, supported by an auto defrost function, provides precise monitoring, ensuring drinks are kept at perfect

### PRODUCT OPTIONS AND ACCESSORIES

A12/092/Z1 Wire Shelf - Chrome - for M90 Bottle Cooler

### **PRODUCT FEATURES**

- Reduced 850mm height
- Wide range of options available to customise your bottle cooler, ensure a perfect fit in any bar.
- Elegant, flexible storage for up to 117 bottles
- Dynamic Air Distribution System coupled with efficient compressors and improved insulation ensures superior cooling times.
- Electronic temperature control keeps drinks at the perfect serving temperature
- Energy efficient EcoSmart controller at the touch of a button, put the bottle cooler into its most economical state until next required
- Sleek stainless steel interior and LED lighting to enhance display
- Twin double-glazed lockable doors for enhanced security
- UK 3 pin plug allows users to simply plug in and switch on







### IMC VENTUS V90 BOTTLE COOLER [FRONT LOAD] - GLASS DOOR -BLACK PAINTED FRAME - H 850 MM - W 900 MM - R290

# MODEL: F76/251/B

WEIGHTS & DIMENSIONS	
Width	900 mil
Depth	500 mil
Height	850 mil
Weight	76.5 kg

SHIPPING DETAILS	
Ship Width	96 cm
Ship Depth	58 cm
Ship Height	109 cm
Ship Weight	84.15 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

### **PRODUCT CERTIFICATIONS**



ENERGY SPECS	
Primary Energy Type	Electric
Electrical Total Amperage	1.71 A
Electrical Volts	240V
Electrical Total Wattage	410 W
Electrical Kilowatts	0.41 kW
Electrical Phase	1-Phase
Electrical Plug Type	UK 3-Pin Plug

Number of Electrical Plugs	1
Electrical Connection Type	Cord and Plug
Number of Electrical Conductor Wires	1
Dedicated Circuit Required	No
Electrical Remarks	Single
Energy Saving	Yes

ADDITIONAL SPECIFICATIONS	
Application Type	Undercounter
Capacity: Bottles	117
Capacity Volume	185 l
Control Type	Digital Touch Pad, Elec- tronic
Defrost Method	Automatic
Insulated	Yes

Legs or Casters	Not Applicable
Number of Shelf Positions	29
Number of Shelves	2
Refrigerant Type	R-290
Temperature Maximum	6 °C
Temperature Minimum	2 °C
Type of Lighting	LED

### **BIDDING SPECIFICATIONS**

Bidding Specifications Not Available.

IMC reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.


Document Auto-Generated July 02, 2024







MODEL: F76/251/B

### **TECHNICAL DRAWING**







IMC reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated July 02, 2024

