



Opus 800

Designed for quality cooking at speed, the Opus 800 Gas Chrome Griddle heats up quicker than standard griddles with less energy loss as well as reduced energy radiation, keeping the kitchen cooler for staff and reducing pressure on the ventilation system. Heat is transferred more efficiently than with a standard griddle, while the chrome griddle also comes with two separately controlled heat zones, which allow for the versatility of operating either zone independently when cooking two separate meals simultaneously. Perfect for any busy commercial kitchen, the griddle also comes with convenient piezo ignition, pilot burners for stand-by operation, and flame failure protection for added safety.

PRODUCT OPTIONS AND ACCESSORIES

- CH01 CATERFLEX HOSE 1/2" 1 METRE
- CH02 CATERFLEX HOSE 1/2" 1.5 METRE
- OA8914/C Lincat Opus 800 Free-standing Floor Stand with Castors - for units W 900 mm
- OA8914 Lincat Opus 800 Free-standing Floor Stand with Legs - for units W 900 mm
- OA8973/C Lincat Opus 800 Free-standing Pedestal with Doors and Castors - for units W 900 mm
- OA8973 Lincat Opus 800 Free-standing Pedestal with Doors and Legs - for units W 900 mm

PRODUCT FEATURES

- Chrome surface heats up quicker than standard griddles with less energy loss as well as reduced energy radiation, keeping the kitchen cooler for staff and reducing pressure on the ventilation system
- Transfers heat to food more efficiently than a standard griddle
- Two separately controlled heat zones give you the option of operating either zone independently to provide a smaller cooking area during quiet periods as well as offering versatility when cooking two separate meals simultaneously
- Convenient piezo ignition and pilot Burners for stand-by operation
- Flame failure protection

WEIGHTS & DIMENSIONS

Width	900 mm
Depth	800 mil
Height	532 mm
Weight	108 kg

SHIPPING DETAILS

Ship Width	100 cm
Ship Depth	800 cm
Ship Height	63 cm
Ship Weight	118.8 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Source Type	Gas	Gas Inlet Size	0.5 in
Kilowatts	23 kW	Gas Inlet Pressure Required	37 mBar
Electrical Connection Type	Not Applicable	Gas Total BTUs	78476 BTU
Electrical Plug Type	Not Applicable	Gas Consumption at Max Use Per Hour	1.64 m ³
Number of Electrical Plugs	Not Applicable	Total Heat Input at Max Use	24 kW
Dedicated Circuit Required	Yes	Energy Saving	No
Gas Type	Propane		

ADDITIONAL SPECIFICATIONS

Control Type	Mechanical	Number of Burners	2
Cooking Area Plate Depth	600 mm	Number Of Controls	2
Cooking Area Plate Width	890 mm	Number of Heating Zones	2
Cooking Plate Finish Material Type	Steel Plate	Plate Shape	Rectangle
Food Production Rate	160 x 225g [8oz] steaks [chilled] per hour	Plate Thickness	15 mm
Legs or Casters	Not Applicable	Temperature Maximum	280 °C
Lower Platen Surface Type (multi-select)	Smooth	Temperature Minimum	90 °C
		Thermostat Element Location	Under Plate Mount

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

